



SUCCEED AT THE  
**FIRST ATTEMPT!**

<https://developer certification.com>



Questions and Answers Demo PDF

# **Dell EMC**

## **DES-1241 Exam**

**Dell EMC Specialist - Platform Engineer, PowerStore Version 1.0  
Exam**

**Questions & Answers  
Demo**



# Version: 4.0

---

**Question: 1**

---

What describes Dell EMC PowerStore X front-end cabling?

- A. Uses internal VMware virtual switching and does not require a management network
- B. Storage and management use the same LACP bonded cable connection
- C. Uses VLTi data switch interconnectivity to support vMotion networks
- D. Management and discovery use the same cables and connections as storage

---

**Answer: C**

---

---

**Question: 2**

---

Through which network do external hosts connect to the cluster for data access?

- A. Management
- B. ICM
- C. ICD
- D. Storage

---

**Answer: D**

---

Reference:

[https://topics-cdn.dell.com/pdf/pwrstr-hcg\\_en-us.pdf](https://topics-cdn.dell.com/pdf/pwrstr-hcg_en-us.pdf)

---

**Question: 3**

---

A Storage Administrator is adding an appliance into an existing Dell EMC PowerStore T cluster. What is different about the management network configuration for the new appliance compared to configuring an initial appliance for the cluster?

- A. All the needed management IP addresses for the new appliance must be pre-configured on the cluster
- B. Additional appliance does not require a cluster management IP address
- C. Additional appliance inherits all its management IPs from the existing appliance
- D. All the needed management IP addresses for the new appliance are auto-generated by the cluster

---

**Answer: D**

---



---

**Question: 4**


---

DRAG DROP

When connecting a PowerStore base enclosure to 2 expansion enclosures, match the base SAS ports in column A to their corresponding expansion LCC ports in column B.

Base SAS Ports	Expansion LCC Ports
Node B SAS B	Exp 1 LCC A port A
Node A SAS A	Exp 2 LCC B port B
Node A SAS B	Exp 1 LCC B port A
Node B SAS A	Exp 2 LCC A port B

---

**Answer:**


---

Node A SAS B
Node A SAS A
Node B SAS B
Node B SAS A

Reference:

<https://www.dell.com/support/manuals/pk/en/pkbsd1/powerstore-1000/pwrstr-isg/cable-the-base-enclosure-to-the-expansion-enclosure?guid=guid-d68d049f-2b77-489f-b1ab-553f4f3de8aa&lang=en-us>

---

**Question: 5**


---

What is the last step when adding a drive to a Dell EMC PowerStore system?

- A. Verify the new drive is seen
- B. Add the drive to the pool



- C. Backup the keystore
- D. Zero the drive

---

**Answer: A**

---

Reference:

<https://www.dell.com/support/manuals/pk/en/pkbsd1/powerstore-9000t/pwrstr-isg/install-a-25-drive?guid=guid-bddae51e-a561-4e84-bc0a-c2e99a43f033&lang=en-us>





<https://developer certification.com>